

LANÇAMENTO DONNER LINE ARRAY COLUMN

O Sistema de Colunas Donner proporciona excelente desempenho, com excepcional inteligibilidade e fidelidade de voz. Em atrativo gabinete de aço com pintura epóxi, seu revestimento garante profundidade e dinâmica a níveis elevados. As Colunas Donner possuem entradas e saídas com conectores Speakon e suporte de parede ajustável. Disponíveis nos modelos com 4, 8 e 12 alto falantes, as colunas passivas Donner são ideais para sonorização de ambientes de pequeno e médio porte.



MODEL C425

Power-handling nominal (RMS)	100 W RMS @ 8 Ω
Nominal impedance	8 Ω
Sensitivity 1W/1m	89 dB (half space)
Frequency response -10 dB	160 Hz – 16 kHz
Speaker	4 x 4" broadband
Directivity	70° horizontal
Recommended crossover frequency	140 Hz, 12 dB/oct. HP
Connections	1 x SPEAKON-Connect-In 1 x SPEAKON-Connect-Out
Dimensions (WfxHxDxWb)	15 x 45,5 x 15,5 x 9,5 cm
Weight	5,5 kg

MODEL C825

Power-handling nominal (RMS)	200 W RMS @ 8 Ω
Nominal impedance	8 Ω
Sensitivity 1W/1m	90 dB (half space)
Frequency response -10 dB	150 Hz – 16 kHz
Speaker	8 x 4" broadband
Directivity	70° horizontal
Recommended crossover frequency	140 Hz, 12 dB/oct. HP
Connections	1 x SPEAKON-Connect-In 1 x SPEAKON-Connect-Out
Dimensions (WfxHxDxWb)	15 x 88,5 x 15,5 x 9,5 cm
Weight	10,6 kg

MODEL C1225

Power-handling nominal (RMS)	300 W RMS @ 8 Ω
Nominal impedance	8 Ω
Sensitivity 1W/1m	92 dB (half space)
Frequency response -10 dB	150 Hz – 18kHz
Speaker	12 x 4" broadband
Directivity	70° horizontal
Recommended crossover frequency	140 Hz, 12 dB/oct. HP
Connections	1 x SPEAKON-Connect-In 1 x SPEAKON-Connect-Out
Dimensions (WfxHxDxWb)	15 x 130,5 x 15,5 x 9,5 cm
Weight	15,3 kg

DONNER